



Chainsaw cross-cutting and manual stacking



Notes

Further reading

<i>Using petrol-driven chainsaws</i>	AFAG301
<i>Basic chainsaw felling and manual takedown</i>	AFAG302
<i>Chainsaw snedding</i>	AFAG303
<i>Chainsaw clearance of windblow</i>	AFAG306
<i>Chainsaw felling of large trees</i>	AFAG307
<i>Use of winches in directional felling and takedown</i>	AFAG310
<i>Emergency planning</i>	AFAG802
<i>Electricity at work: Forestry and arboriculture</i>	AFAG804
<i>Watch your back: Avoiding back strain in timber handling and chainsaw work</i>	INDG145
<i>First aid at work: Your questions answered</i>	INDG214
<i>Managing health and safety in forestry</i>	INDG294
<i>Chainsaws at work</i>	INDG317
<i>Protect your hearing or lose it!</i>	INDG363

These publications are available from HSE Books - see 'Further information'.

Notes

Name:.....
 Checklist verified by:.....
 Date:.....

Further information

HSE priced and free publications are available by mail order from HSE Books, PO Box 1999, Sudbury, Suffolk CO10 2WA
 Tel: 01787 881165 Fax: 01787 313995 Website: www.hsebooks.co.uk
 (HSE priced publications are also available from bookshops and free leaflets can be downloaded from HSE's website: www.hse.gov.uk.)

For information about health and safety ring HSE's Infoline
 Tel: 0845 345 0055 Fax: 0845 408 9566 Textphone: 0845 408 9577
 e-mail: hse.infoline@natbrit.com or write to HSE Information Services,
 Caerphilly Business Park, Caerphilly CF83 3GG.

This leaflet contains notes on good practice which are not compulsory but which you may find helpful in considering what you need to do.

This leaflet is available in priced packs of 15 from HSE Books, ISBN 978 0 7176 2639 7. Single free copies are also available from HSE Books.

© *Crown copyright* This publication may be freely reproduced, except for advertising, endorsement or commercial purposes. First published 04/03. Please acknowledge the source as HSE.

Printed on paper made using 50% recycled fibre from post-consumer sources.

AFAG304 Reprinted 05/09 C150

Printed and published by the Health and Safety Executive

Introduction

This leaflet covers the safe working practices to be used when cross-cutting and stacking timber. For guidance on personal protective equipment (PPE), the machine, preparing to work, maintenance, fuelling and starting procedures see AFAG leaflet 301 *Using petrol-driven chainsaws*.

You can use this leaflet, along with the chainsaw manufacturer's handbook, as part of the risk assessment process to help identify the controls to put in place when cross-cutting and stacking.

You must also assess the effect of the site and the weather as well as following this guidance.

All operators must have had appropriate training in how to operate the machine and how to carry out the tasks required (see HSE leaflet INDG317 *Chainsaws at work*).

Preparing to cross-cut and stack

- 1 Clear any debris that is likely to interfere with the cross-cutting process.
- 2 Plan the work so that the lightest produce moves furthest.
- 3 Use bearers or other supports where possible.
- 4 Ensure the work area gives a good firm footing.
- 5 A length of timber should only be broken down into sections by one person at any one time.
- 6 Ensure that a safe working distance is maintained between workers (at least 5 m) and between workers and machinery (outside the risk zone of the machines being used).
- 7 Maintain a secure and balanced stance.
- 8 When cross-cutting on slopes, work on the uphill side of logs if there is a risk of the timber rolling.





Figure 2 Start of boring cut



- 9 Reduce excessive tension by first making a cut on the compression side of the log (see Figure 1).
- 10 When it is necessary to use a boring cut, do not start with the tip of the guide bar and ensure that it does not strike other stacked material as this can cause kickback (see Figure 2).
- 11 If the chainsaw jams, switch it off. Pull the chainsaw gently to see if it can be dislodged, otherwise use the correct aid tools to open the cut.
- 12 Be ready to step back quickly if the log being cut starts to roll.

Manual handling and stacking

- 13 Follow best practice when manual handling (see HSE leaflet INDG145 *Watch your back*).

- 14 Use appropriate aid tools for lifting and moving timber, eg pulp hooks, lifting tongs, cant hooks and pickaroons.
- 15 Stack cut material frequently so that it does not create a hazard underfoot.
- 16 Stacks of timber should always be made and maintained in a stable condition. Do not stack on steep ground at the roadside.
- 17 Where stacks are manually produced, the height of the stacked timber should not exceed about 1 m. Otherwise, so far as is reasonably practicable, stack heights should not exceed 2 m.
- 18 Take special care in areas frequented by the public. Where appropriate, although not a substitute for safe stacking, a warning sign conforming to the Health and Safety (Safety Signs and Signals) Regulations 1996 should be displayed, and/or the site enclosed with hazard warning tape.





Figure 1 Identification of tension and compression wood