

FIGURES

- Figure 1: Photograph of the apparatus used for tensile testing
- Figure 2: Photograph of a webbing gripped for testing
- Figure 3: Schematic diagram of webbing and grip arrangement
- Figure 4: Test data set for as received webbing 1
- Figure 5: Test data set for as received webbing 2
- Figure 6: Test data set for as received webbing 3
- Figure 7: Test data set for as received webbing 4
- Figure 8: Test data set for as received webbing 5
- Figure 9: Test data set for as received webbing 6
- Figure 10: Test data set for as received webbing 7
- Figure 11: Test data set for as received webbing 8
- Figure 12: Test data set for as received webbing 9
- Figure 13: Test data set for as received webbing 10
- Figure 14: Schematic diagram of rig used for the ingress of dirt
- Figure 15: Particle size distribution for sand used for the ingress of dirt
- Figure 16: The change in the appearance of a representative webbing with increasing levels of damage by ingress of dirt
- Figure 17: The effect of ingress of dirt on a typical webbing (webbing 1)
- Figure 18: The effect of ingress of dirt on the maximum load withstood by all webbings
- Figure 19: Strength loss (as a % of original strength) of all webbings after ingress of dirt
- Figure 20: The effect of ingress of dirt on the elongation of all webbings
- Figure 21: The effect of ingress of dirt on the energy absorbed by all webbings
- Figure 22: Photograph of a typical failure of a webbing damaged by the ingress of dirt

- Figure 23: The change in the appearance of a typical webbing with increasing levels of edge damage
- Figure 24: The effect of edge damage on a typical webbing (webbing 1)
- Figure 25: The effect of edge damage on the maximum load withstood by all webbings
- Figure 26: Strength loss (as a % of original strength) of all webbings after edge damage
- Figure 27: The effect of edge damage on the elongation of all webbings
- Figure 28: The effect of edge damage on the energy absorbed by all webbings
- Figure 29: Photograph of a typical failure of a webbing damaged at the edge
- Figure 30: Photograph of the Sol 2 sunlight simulation unit as used for exposing samples to ultraviolet radiation
- Figure 31: Photograph showing the positioning and "wrapping" of a sample in the unit prior to exposure
- Figure 32: The change in the appearance of a typical webbing with increasing levels of exposure to ultraviolet radiation
- Figure 33: The effect of exposure to ultraviolet radiation on a typical webbing (webbing 1)
- Figure 34: The effect of exposure to ultraviolet radiation on the maximum load withstood by all webbings
- Figure 35: Strength loss (as a % of original strength) of all webbings after exposure to ultraviolet radiation
- Figure 36: The effect of exposure to ultraviolet radiation on the elongation of all webbings
- Figure 37: The effect of exposure to ultraviolet radiation on the energy absorbed by all webbings
- Figure 38: Photograph of a typical failure of a webbing exposed to ultraviolet radiation
- Figure 39: Results of transmission of light through flat glass sample tests, represented graphically as % transmission of light
- Figure 40: Photograph to show method of exposing samples to sunlight

- Figure 41: The change in the appearance of a typical webbing with increasing levels of exposure to sunlight only
- Figure 42: The effect of exposure to sunlight on a typical webbing (webbing 1)
- Figure 43: The effect of exposure to sunlight on the maximum load withstood by all webbings
- Figure 44: Strength loss (as a % of original strength) of all webbings after exposure to sunlight
- Figure 45: The effect of exposure to sunlight on the elongation of all webbings
- Figure 46: The effect of exposure to sunlight on the energy absorbed by all webbings
- Figure 47: Photograph of a typical failure of a webbing exposed to sunlight
- Figure 48: Photograph to show method of exposing samples to all weather conditions
- Figure 49: The change in the appearance of a typical webbing with increasing levels of exposure to all weather conditions
- Figure 50: The effect of exposure to all weather conditions on a typical webbing (webbing 1)
- Figure 51: The effect of exposure to all weather conditions on the maximum load withstood by all webbings
- Figure 52: Strength loss (as a % of original strength) of all webbings after exposure to all weather conditions
- Figure 53: The effect of exposure to all weather conditions on the elongation of all webbings
- Figure 54: The effect of exposure to all weather conditions on the energy absorbed by all webbings
- Figure 55: Photograph of a typical failure of a webbing exposed to all weather conditions
- Figure 56: Harness 1 - Examination of damage sustained in-service
- Figure 57: Harness 2 - Examination of damage sustained in-service
- Figure 58: Harness 3 - Examination of damage sustained in-service
- Figure 59: Colour approximations for typical webbing samples after damage/exposure

Figure 60: Examination of damage sustained after the ingress of dirt (ID 3)

Figure 61: Examination of damaged sustained after exposure to all weather conditions (AW 3)

Figure 62: Comparison of colour change effects of different exposures with the change in tensile strength of webbings