

BK4

COSHH essentials in brick and tile making: Silica



This information will help employers (including the self-employed) comply with the Control of Substances Hazardous to Health

Regulations 2002 (COSHH), as amended, to control exposure to respirable crystalline silica (RCS) and protect workers' health.

It is also useful for trade union safety representatives.

This sheet describes good practice using engineering control - a filtered air supply to the vehicle cab.

It covers the points you need to follow to reduce exposure to an adequate level.

It is important to follow all the points, or use equally effective measures.

Main points

- High dust levels result from ash and brick-dust, and vehicles crushing clay, brick and ash.
- Breathing in dust may cause silicosis.
- Keep exposure as low as possible using all the controls in this sheet. Make sure the controls work.
- You need air sampling. See sheet G409.
- Health surveillance is usually needed. See sheet G404.

Moving green and fired bricks

Control approach 2 Engineering control

Hazard

- ✓ Brick and tile making can produce airborne respirable crystalline silica (RCS).
- ✓ All RCS is hazardous, causing silicosis. This is a serious lung disease causing permanent disability and early death.
- ✓ Silicosis is made worse by smoking.
- ✓ 'Respirable' means that the dust can get to the deepest parts of the lung. Such fine dust is invisible under normal lighting.
- ✓ Keep inhalation of RCS as low as possible.
- ✓ When all controls are applied properly, less than 0.1 mg/m³ RCS is usually achievable (based on an 8-hour time-weighted average).

Crystalline silica concentrations in common materials

- ✓ See table in sheet BK0.

Access and premises

- ✓ Only allow access to authorised staff.
- ✓ Prevent other people from approaching the working zone.

Equipment

- ✓ Vehicle movements crush green and fired brick wastes and generate dust.
- ✓ Use vehicles fitted with a clean air supply to the cab. See sheet BK7.
- ✓ Alternatively, provide a supply of clean air to blow down over the driver at a speed between 0.5 and 1 metres per second.
- ✓ Fit an indicator or alarm to show if filters have blocked or failed.
- ✓ Wash down metalled roadways regularly and limit vehicle speed.

Procedures

- ✓ Always confirm that the control cab air supply is turned on and working before starting work.
- ✓ Keep cab doors and windows closed while working.
- ✓ Make sure you can get spares easily.

Maintenance, examination and testing

- ✓ Minerals and silica-containing dusts are very abrasive. Plan regular maintenance.
- ✓ Follow instructions in maintenance manuals - keep equipment in effective and efficient working order.
- ✓ Clean down before starting maintenance - use wet or dustless methods. See sheet BK7.

-
- ✓ Review records - failure patterns show where preventive maintenance is needed.
 - ✓ Carry out air sampling to check that the controls are working well. See sheet G409.

Personal protective equipment (PPE)

- ✓ Ask your supplier to help you select the right PPE.
- ✓ Provide storage for clean and contaminated PPE.

Respiratory protective equipment (RPE)

- ✓ RPE should not be needed inside the cabin if the filtered air supply is working properly and the doors and windows are shut.
- ✓ Can you avoid driving vehicles while wearing RPE?

Other protective equipment

- ✓ Provide coveralls that do not retain dust. Use synthetic fabrics - not cotton or knitted.
- ✓ Skin creams help in washing contamination from the skin. After-work creams help to replace skin oils.

Caution: Never allow use of compressed air for removing dust from clothing.

Health surveillance

- ✓ You need health surveillance unless exposure to RCS is well below the limit. See sheet G404.
- ✓ Consult an occupational health professional - see 'Useful links'.

Cleaning and housekeeping

- ✓ See sheet BK7 for vehicle cabs.
- ✓ Clean the control cab at least once a week. Fine dust on internal surfaces suggests poor control.
- ✓ Use a Type H vacuum cleaner fitted with a HEPA filter, or wet clean


Caution: Don't use a brush or compressed air.

Training and supervision

- ✓ Tell workers that silica dust can cause serious lung diseases.
- ✓ Working in the right way and using the controls correctly is important for exposure control. Train and supervise workers. See sheet BK0.

Further information

- *Control of respirable silica dust in heavy clay and refractory processes* HSG72 HSE Books 1992 ISBN 0 11 885679 0
- *Health surveillance: A ceramics industry booklet* Leaflet IACL100 HSE Books 1996 (single copy free)
- For environmental guidelines see sheet BK0



Useful links

- The British Ceramics Confederation (BCC) may advise on health and safety consultants and training providers. Website: www.ceramfed.co.uk
- For information about health and safety, or to report inconsistencies or inaccuracies in this guidance, visit www.hse.gov.uk/. You can view HSE guidance online and order priced publications from the website. HSE priced publications are also available from bookshops.
- Contact the British Occupational Hygiene Society (BOHS) on 01332 298101 or at www.bohs.org for lists of qualified hygienists who can help you.
- Look in the Yellow Pages under 'Health and safety consultants' and 'Health authorities and services' for 'occupational health'.
- Also see www.nhsplus.nhs.uk.

Employee checklist

- Are you sure how to use all dust controls?
- Is the cab clean air supply working? Are the windows shut?
- Look for signs of leaks, wear and damage every day.
- If you find any problems, tell your supervisor. Don't just carry on working.
- Make suggestions to improve the effectiveness of dust control.
- Co-operate with health surveillance.
- Use, maintain and store your protective equipment in accordance with instructions.
- Use skin creams provided as instructed.

This document is available at: www.hse.gov.uk/pubns/guidance/ and www.hse.gov.uk/coshh/essentials/

This document contains notes on good practice which are not compulsory but which you may find helpful in considering what you need to do.

© Crown copyright If you wish to reuse this information visit www.hse.gov.uk/copyright.htm for details. First published 10/06