

RB6

COSHH essentials for
rubber manufacturers

Trimming and finishing (small articles)

Control approach 2 Engineering control

The Control of Substances Hazardous to Health Regulations 2002 (COSHH) require employers to ensure that exposure is prevented or, where this is not reasonably practicable, adequately controlled. This guidance gives practical advice on how this can be achieved by applying the principles of good practice for the control of exposure to substances hazardous to health, as required by COSHH.

It is aimed at people whose responsibilities include the management of substances hazardous to health at work (eg. occupational health specialists, anyone undertaking COSHH assessments and supervisors). It is also useful for trade union and employee safety representatives. It will help you carry out COSHH assessments, review existing assessments, deliver training and supervise activities involving substances hazardous to health.

This guidance is issued by the Health and Safety Executive. Following the guidance is not compulsory, unless specifically stated, and you are free to take other action. But if you do follow the guidance, you will normally be doing enough to comply with the law. Health and safety inspectors seek to secure compliance with the law and may refer to this guidance.

See Essential information near the end of the sheet.

What this sheet covers

This sheet describes good control practice using fume extraction when trimming and finishing small rubber articles.

It covers the key points to follow to reduce exposure to an adequate level.

Follow all the points, or use equally effective measures.

Main points

- Trimming and finishing hot articles can produce high levels of fume. This sheet focuses on reduction of exposures to rubber fume.
- Rubber dust, produced during, eg. buffing activities, may be, or become, hazardous to health and need to be considered as part of a COSHH risk assessment. Exposure should be prevented, or adequately controlled, using suitable engineering measures such as local exhaust ventilation (LEV) and/or on-tool extraction methods.
- Keep exposures as low as reasonably practicable using all the controls in this sheet.
- Make sure the controls work.
- Consider health surveillance for dermatitis. See sheet G403 for advice on the health surveillance you may need to put in place.

Hazards

- ✓ Rubber fume is released when making natural or synthetic rubber, and when moulding or extruding to convert blended ingredients into finished parts or products.
- ✓ Chronic inhalation exposure to rubber dust and fume in rubber factories can cause higher than normal incidence of some types of cancers.
- ✓ Skin exposure to rubber dust and fume may cause dermatitis and skin allergies.
- ✓ The workplace exposure limit (WEL) of rubber process dust is detailed in HSE publication [EH40/2005 Workplace Exposure Limits](#)


Access to work area

- ✓ Allow access to authorised and appropriately trained people only.

Equipment and procedures

- ✓ Leave items in the mould to lose their initial burst of fume, provided the opened mould is in a suitable enclosure with effective LEV.
- ✓ Keep the transfer time from the mould to the workstation as short as possible, or extract fume given off from hot mouldings, eg. on an enclosed conveyor/tunnel.

- ✓ Provide an extracted workstation for hot trimming and finishing, which includes a lidded bin for trimmings (flash, sprue, runners or scrap) inside the enclosure.
- ✓ Enclose the workstation as much as possible. Use a clear screen/view panel between the hot workpiece and the worker's face. A flexible strip curtain with overlapping strips should also be fitted at the workstation opening to stop fumes escaping.
- ✓ Airflow must be sufficient to control airborne contaminants effectively. This will depend on the design, size of opening and the type of process and substance being controlled.
- ✓ Provide an easy way of checking the LEV is working, eg. airflow indicator or equivalent.
- ✓ Discharge extracted air to a safe place away from doors, windows and air inlets.
- ✓ Provide adequate clean 'make up air' into the workplace to replace extracted air.
- ✓ Consult a qualified ventilation engineer to design new control systems and to update current controls.
- ✓ Always confirm that the extraction is turned on and working at the start of work.
- ✓ Put trimmings and waste in the bin and replace the lid.



Respiratory protective equipment (RPE)

- ✓ RPE is normally not needed.
- ✓ RPE is usually needed for maintenance and cleaning.


Personal protective equipment (PPE)

- ✓ Ask your supplier to advise on suitable PPE.
- ✓ Provide chemical- and heat-resistant protective gloves – seek advice from your supplier.
- ✓ Use a contract laundry or a suitable equivalent to wash work clothing. Don't allow workers to do this at home.

Personal decontamination and skin care

- ✓ Provide warm water, mild skin cleansers, and soft paper or fabric towels for drying. Avoid abrasive cleansers.
- ✓ Provide pre-work skin creams, which will make it easier to wash dirt from the skin.
- ✓ Provide after-work creams to replenish skin oils.

Caution: 'Barrier creams' are not 'liquid gloves' and do not provide a full barrier.



Maintenance, examination and testing

- ✓ Keep all equipment used in the task in effective working order. Maintain it as advised by the supplier or installer.
- ✓ Check for signs of damage to control equipment before starting work.
- ✓ Check transfer hoses and connectors regularly for leaks.
- ✓ At least once a week, check that any airflow indicators work properly.
- ✓ Have equipment thoroughly examined and tested against its performance standard, at suitable intervals.
- ✓ For LEV, a user manual or log book is helpful in setting out the frequency of checking, maintenance or parts replacement.
- ✓ For LEV with no user manual or log book, you may need the help of a competent person. They can determine the performance needed for adequate control.
- ✓ LEV systems require a statutory 'thorough examination and test' (TExT).
- ✓ Get a competent person to perform the TExT at least once every 14 months.
- ✓ Carry out all actions arising from the TExT.
- ✓ Several measures are available to check effectiveness of controls, ranging from simple qualitative (eg. use of a dust lamp) to complex quantitative techniques (eg. air sampling) usually for higher-risk scenarios.

Cleaning and housekeeping

- ✓ Clean work equipment and the work area daily. Clean other equipment and the workroom regularly at least once a week.
- ✓ Use at least a Class M vacuum cleaner to clear up dust.
- ✓ Store containers in a safe place and keep them lidded when they are not in use.

Caution: Never allow the use of a brush or compressed air for removing dust from skin and clothing. Avoid the use of a brush or compressed air for removing dust from surfaces or from inside machinery.

Health surveillance

- ✓ Provide health surveillance for dermatitis where there is a reasonable likelihood that dermatitis may occur in your workplace. See sheet G403.

Training and supervision

- ✓ Provide supervision – ensure that safe work procedures are followed.
- ✓ Tell workers about the hazards associated with their work and how to recognise early signs of asthma and dermatitis.
- ✓ Provide workers with training on:
 - working safely with hazardous substances;
 - when and how to use controls;
 - how to check they are working;
 - how the LEV system works;
 - how to use the LEV to get the best out of it;
 - how to check that the LEV is working;
 - what to do if something goes wrong.
- ✓ Training records are helpful to demonstrate training has taken place.

- ✓ Changes to the work process and LEV mean that staff may need retraining.
- ✓ Involve managers and supervisors in health and safety training.

Essential information

You can find the full COSHH essentials series at www.hse.gov.uk/coshh/essentials/index.htm

Health surveillance for occupational dermatitis COSHH Guidance Sheet G403 HSE Books 2011 www.hse.gov.uk/pubns/guidance/g403.pdf

New and existing engineering control systems COSHH Guidance Sheet G406 HSE Books 2011 www.hse.gov.uk/pubns/guidance/g406.pdf

Exposure measurement: Air sampling COSHH Guidance Sheet G409 HSE Books 2011 www.hse.gov.uk/pubns/guidance/g409.pdf

Further information

Occupational Safety and Health Consultants Register: www.oshcr.org/

Safe to breathe: Dust and fume control in the rubber industry, Leaflet IACL95, HSE 1995, www.hse.gov.uk/pubns/rubindex.htm

The British Tyre Manufacturers Association (BTMA): www.btmauk.com

The British Rubber & Polyurethane Products Association (BRPPA): www.brppa.co.uk

Retread Manufacturers Association: <http://www.retreaders.org.uk/>

For information about health and safety visit <https://books.hse.gov.uk> or <http://www.hse.gov.uk>

You can view HSE guidance online and order priced publications from the website. HSE priced publications are also available from bookshops.

To report inconsistencies or inaccuracies in this guidance, email: commissioning@wlt.com

Employee checklist

- Is the extraction working?
Is there any obvious dust on work surfaces and ledges?
- Tidy up flash, ie. trimmings or other rubber waste, immediately.
- Look for signs of leaks, wear and damage before every job. If you find any problems, tell your supervisor. Don't just carry on working.
- Co-operate with health surveillance.
- Use, maintain and store your PPE in accordance with instructions.
- Discard protective gloves in accordance with manufacturer's instructions.
- Wash hands before eating, drinking, smoking, using the lavatory and after work.
- Never use solvents to clean your skin.
- Use skin creams provided as instructed.